

# Product-Information

## Alu-Preservative PU

### GRM listed protection for PU- and lacquer-coatings

Properties : Alu-Preservative PU is used as a protective film for cleaned powder and lacquer-coated surfaces, as well as surfaces in alloy steel, copper and brass.

Alu-Preservative PU forms a temporary weather and UV-resistant protective film. The product is polishable and leaves behind a silky shining film. Moreover the layer is uniform and iridescent. It removes at the same time light dirt on the surface. Moreover, It is easy to remove graffiti on surfaces already treated with Alu-Preservative PU.

Chem. characteristics: Silicone oil in solvent  
contains inflammable, non toxic solvent

Dosage : pure

Directions for use: Shake very well Heidt & Schwarzfeld Alu-Preservative PU before using. Apply in a thin layer Alu-Preservative PU on the dry surface by using a soft and absorbent cloth. Then light polish with a soft absorbent cloth while the surface is still humid.

Application: approx. 30 up to 60g/m<sup>2</sup>

Note: Do not use Alu-Preservative PU into direct sunlight or on heated plates. Do not use at a temperature below + 10° C.

Please follow carefully the instructions and safety recommendations out of the EU-regulations form.

Specifications:	Expiration	minimum of 2 years
	pH-value	none
	Contents	solution of wax and silicone oil in special benzine

Barrel size: 10 l/Barrel

UN-Number:	1223
UBA-Number:	12670018
GRM-Registrationnr.	205
Item-Number:	10206

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.