

Product-Information

Alu-WK 100

Detergent insensitiv lustre preservative

Properties : Detergent insensitiv is suitable for lacquered surfaces, aluminium, chrome, copper, brass and for sealing up glass surfaces. Alu-WK 100 does not only keep shining treated external facades of lacquered metal surfaces or aluminium but is also detergent-resistant. Alu-WK 100 contains an outstanding absorption with an extreme longlasting protection.

The protective film on the treated external facades lasts after 50 times being cleaned with a water containing a detergent. The detergent-resistance evolves after 4 hours and reaches its maximum value after 12 hours. Alu-WK 100 intensifies the colour shade.

Dosage : pure or diluted up to 1:10 with water according to the lustre desired

Directions for use: Shake very well Heidt & Schwarzfeld Alu-WK 100 before using. Distribute Alu-WK 100 with a sprayer or a sponge and quickly wash off with a wet cloth or lambskin cloth.

Application: approximately 30 up to 50 g/m²

Note: Do not use Alu-WK 100 during periods of direct insolation or on heated plates. Do not use at a temperature below + 10°C. Please do use the already diluted preservative within 3 days.

Please follow carefully the instructions and safety recommendations out of the EU-regulations form.

Specifications:	Expiration	minimum of 2 years
	pH-value	5-6
	Contents	solvent. silicone oil

Barrel size: 10 l/Barrel

UN-Number:	1219
UBA-Number:	12670015
Item-Number:	10211

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.