

Product-Information

Graffiti Schutz (anti graffiti)

Special coating against graffiti contamination

- Properties : Graffiti-Schutz can be used for treatment of mineral building materials such as sand-lime brick, bricks, natural stone, plaster and concrete on walls and for sculptures, monuments and stove-enamele metal surfaces: Not suitable in ground areas or on coated walls.
Graffiti-Schutz is a watery, milky colourless drying impregnation (which slightly intensifies the shades of colour), as preventive protection against graffiti sprayings. Graffiti-schutz reduces the penetration of water and contaminants on mineral grounds.
- Dosage : pure
- Directions for use: The ground must be free from any structural defects (cracks, sandy joints dampness a.s.o.) and must be clean and dry. Any oil, fat, colour and cleaner residues reduce the effect of Graffiti-Schutz.
- Distribute Graffiti-Schutz well without applying pressure so that a 30-50 cm long fluid film runs down the surface. Lead sprayer horizontally along the facade without interrupting. For smaller surfaces please use well-dipped brush or roll. After applying Graffiti-schutz the surface must be protected against heavy precipitation for at least 5 hours. Strong winds and insolation may accelerate evaporation and reduce the penetration depth.
- Application: approx. 200-500 ml/m² according to the toughness of stain
- Note: Use Graffiti-Schutz only at a temperature range from + 10°C up to 25°C. Protect windows, varnished surfaces, glasses and plants.
- Please follow carefully the user and safety instructions out of the EU-safety regulation form.
- Graffiti-remover: Remove the graffities from the surfaces by spraying hot water vapor ~ 80-90°C (with a high-pressure cleaning equipment). Important: After cleaning and drying apply again Graffiti-Schutz on the surfaces.
- Specifications:
- | | |
|------------|---|
| Expiration | minimum of 1 year (store in a frost-free place) |
| pH-value | neutral |
| Contents | organosiloxan, hydrocarbon |
- Container size: 10 l/Containerl
- | | |
|-----------------|----------|
| UN-Number: | missing |
| UBA-Number: | 12670024 |
| GRM-registernr. | 205 a |
| Item-Number: | 10601 |

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.