

# Product-Information

## Impreg WLN

Properties:	Microemulsion for waterproofing absorbent neutral alkaline reactive grounds.  Impreg WLN is excellent for all kind of natural stones, as well as for concrete, fresh concrete, limesandstone, washconcrete a.s.o. Can be also used indoors.
Chem. characteristics:	highly akali stable
Dosage:	pure
Directions for use:	Generally painted on, sprayed on or rolled in one go. In case of absorbent grounds apply twice wet in wet.
Application:	according to the absorbency of the ground concrete approx. 100 - 200 gr./m <sup>2</sup> limestone/mortar approx. 200 - 250 gr./m <sup>2</sup> gas concrete approx. 300 - 400 gr./m <sup>2</sup> natural stone/bricks approx. 200 - 400 gr./m <sup>2</sup>
Note:	Do not use at a temperature below The lower the temperatures are, the longer the reaction tim+5°C. Frost-free and do not store for a long period at a temperature above +30°C. For best result test previously on a sample.  Please follow carefully the instruction and safety recommendations out of the EU-safety regulation form.
Specifications:	Expiration: minimum of 3 months pH-value: 6,7 contents: alkylalkoxysilane/siloxane
container size:	20 ltr./container  UN-Number missing UBA-Number 12670051 Item Number10304

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.