

Product-Information

Facades Protection PM-21 GRM listed eloxal and PU-Preservative

Properties: Facades Protection PM-21 is an excellent facade protection product for eloxal, PU-coatings and alloy steel, as well as copper, brass, auto varnish and is also used to seal glass surfaces.

Facade Protection PM-21 differs from the traditional facade protection products because of its simple use by all temperature from +5° C up to +70° C and by light precipitation.

Dosage: pure

Directions for use: To be applied in a thin layer with a cloth, lambskin or sponge. After about 5 up to 20 minutes spray off with water or wash off with a wetted lambskin. It leaves a silky shining protective layer. It is not necessary to polish.

Application: approx. 30 up to 60g/m²

Note: Heidt & Schwarzfeld GmbH Facade Protection PM-21 does not contain any solvent and has therefore to be protected from frost.

Please follow carefully the instructions and safety recommendations out of the EU-regulation form.

Specifications:	Expiration	minimum of 2 years
	pH-value	~9
	Contents	emulsion of silicone with stabilizator

Barrel size: 10 l/Barrel

UN-Number:	missing
UBA-Number:	12670050
GRM-registratinnr:	105 f for anodized metal facades
GRM-registratinnr:	205 f for coated metal facades
Item-Number:	10218

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.